



# No Powder White Ink **DTF Printing Solution**

















Phone: +86-371-60301017/60301018

Email: dctec@ink4you.com Website: www.hongsam.cn








Youtube



#### **Process Features:**

- Digital customization: digital transferring process, no plate, no engraving, short process, personalized, immediately available.
- Environmental friendly: water-based environmentally friendly DTF ink, bright color and non-fading, pollution-free production process, guaranteed product safety.
- Features: unique CO ink, design, printing, transferring at one time, no powder, saving process and material costs.
- Return to the original: suitable for various fabrics, leathers, coil plates, does not affect the texture and feel of the original material.
- Color fastness: high textile printing color fastness, high resistance to scratching and bending, good air permeability, high weather resistance, hydrolysis resistance.
- Reasonable structure: the printer and dryer are light in design and compact in structure, saving floor space.
- Intelligent drying: intelligent temperature-controlled hot air circulation system, effective use of heat circulation, save power consumption.
- Intelligent purification: standard patent smoke exhaust system, effectively remove internal moisture, ensure drying effect, small size,

#### **Process Flow:**



## **Printing Principle:**



②White ink layer ③CO ink layer @PFT hot stamping film

Print overlay schematic (print side)

①Color ink printing area

②White ink printing area

③CO ink printing area

Print overlay schematic (side)

### **Parameter specifications:**

Printer				Dryer					
Model	HJ-603			Model	HJ-H602				
Print head	Epson i3200-A1			Drying mode	Intelligent temperature controlled hot air circulation				
Printhead No.	3-4			Drying mode	drying system + front guide plate drying system				
Ink type	Water-based eco-friendly dtf ink			Temperature range	150°C				
Color	KCMY+W+CO,KCMY+W+OP+CO			Drying tunnel Length and Width	W:700mm, L:1150mm				
Printing capacity	Economy mode	4pass	12m²/h	Drying tunnel Height	25mm				
	Production mode	6pass	8m²/h	Loading system	Dual power motor adjustable damping paper stacker				
	Quality mode	8pass	6m²/h	Power	AC220V 50/60HZ		maximum power	8.0KW	
Printing format	600mm			FOWEI			working power	4.9KW	
Printing media	PET film			Equip	oment dimension and weight				
Ink supplying	Big capacity continuous ink supplying system, low liquid level alarm			Working area	W×L	3000*3500mm			
				Printer	W×L×H	V×L×H 1980*1090*1450mm			
White ink system	Intelligent automatic circulation mixing system			Fille	Weight	223KG			
Print head protection	Intelligent dual side high sensitivity anti scratch system			Dryer	W×L×H	H 1640*1140*1120mm			
Printing height	Manual knob adjustable				Weight	236KG			
RIP softwareRIP	R <b>II</b> N,MainTop,PhotoPrint			Equipment dimension and weight					
Printing software	HOSON_PrintExp			Printer	W×L×H 2160*1150*870mm				
Operating system	CPU:i5/i7 RAM:8GB HDD:500GB Win7/10 64bit				Weight	320KG			
Interface	kMbps network			Dryer					
Power	AC220V 50/60Hz 10A,maximum power: 1.2kW				W×L×H	×H 1750*1250*1340mm			
Working environment	temperature:20°C-26°C humidity:35%-65%				Weight	330KG			