

Single pass printer

HONGSAM®

Avoid printhead burning, No air bubble into printhead, More stable.

Product display •



Proofing display •



Product Parameters

Product Name	Single Pass Digital Printer	Ink detection	Ultrasonic Liquid-level Measuring System
Brand	HONG-JET®	Cleaning nozzle method	Key inking
Printhead Model	HJ129HD Industrial Inkjet Head	Ink supply mode	Continuous ink supply
Inkjet Technology	Thermal Inkjet Technolog	Feeder head	Optional and customized
Printing type	one pass	Conveyor	Optional and customized(Suction guide belt type)
Printing resolution	1200x1200DPI/1200x600DPI / 1200x300DPI	Fuselage structure	One-piece cast iron welded frame
Print Speed	10-40 m/min	Beam structure	All aluminum
Core board	HONG-JET® joint development	Regulator	Adjustable mechanical baffle software data positioning
Operating Software	Photoshop	Positioning method	Infrared photoelectric induction positioning
Operating System	win7 win10(Touch screen)	Ink consumption	1 square meter consumes about 8 ml of ink.
Image format	BMP/JPG/PDF/TIFF	Input power supply	220V/110V 50HZ/60HZ
Data transfer	Ethernet/USB3.0/R232	Customized service	YES
Ink type	Dye ink, pigment ink	Thickness of printing material	0.1mm-140mm
Colors	C/M/Y/K	Nozzle to printing Material	1mm-3mm
Application	Corrugated kraft paper, sponge paper, writing paper, rice paper and other surface absorbent materials	Environmental requiremen	Normal temperature 15-35 °C humidity 20% - 80%

HJ129HD Industrial Inkjet Head	No. of Print heads	1	2	3	4	5
	Printing width	12.9cm	25.8cm	38.7cm	51.6cm	64.5cm
	Conveyor Belt Width	80cm	80cm	80cm	80cm	80cm/140cm

Single pass printer

HONGSAM®

Avoid printhead burning, No air bubble into printhead, More stable.

Product display •



Proofing display •



Product Parameters

Product Name	Single Pass Digital Printer	Ink detection	Ultrasonic Liquid-level Measuring System
Brand	HONG-JET®	Cleaning nozzle method	Key inking
Printhead Model	HJ129HD Industrial Inkjet Head	Ink supply mode	Continuous ink supply
Inkjet Technology	Thermal Inkjet Technolog	Feeder head	Optional and customized
Printing type	one pass	Conveyor	Optional and customized(Suction guide belt type)
Printing resolution	1200x1200DPI/1200x600DPI	Fuselage structure	One-piece cast iron welded frame
Print Speed	10-40 m/min	Beam structure	All aluminum
Core board	HONG-JET® joint development	Ink consumption	1 square meter consumes about 8 ml of ink.
Operating Software	Photoshop	Positioning method	Infrared photoelectric induction positioning
Operating System	win7 win10(Touch screen)	Environmental requirements	Normal temperature 15-35 ℃ humidity 20% - 80%
Image format	BMP/JPG/PDF/TIFF	Input power supply	220V/110V 50HZ/60HZ
Data transfer	Ethernet/USB3.0/R232	Customized service	YES
Ink type	Dye ink, pigment ink	Thinkness of printing materia	0.1mm-140mm
Colors	C/M/Y/K	Nozzle to printing Material	1mm-3mm
Application	Corrugated kraft and absorbent materials	Regulator	Adjustable mechanical baffle / software data positioning

HJ129HD Industrial Inkjet Head	No. of Print heads	Printing width	Conveyor Belt Width	Power	Weight	Product size
	1	12.9cm	45cm	0.9kw	675kg	180*100*140cm
	2	25.8cm	45cm	0.9kw	675kg	180*100*140cm